



EAGLE EAGLE SERIES

TILT BED 10K



STANDARD FEATURES

- Adjustable 2 5/16" Coupler
- 7K Drop Leg Tongue Jack
- 2x6 #2 or better Fir Decking
- 4" Drop Axles
- PPG Primer & Paint
- Tube Tongue (Longer than competition)
- New Over Center Latch w/ Release
- 15" Wheels & Tires (Radial)
- Stake Pockets & 4 D-Rings
- Tube Tongue
- Brakes both Axles
- Sealed Beam LED Lights
- Rear Approach Plates 14"
- Cushioning Hydraulic Cylinder

POPULAR OPTIONS

- Pressure Treated Decking
- Removable Fender or Fenders
- Lock-out Valve/Cylinder for multiple pieces of Equipment
- Spare Tire & or Mount
- Tongue Box steel or Aluminum Diamond Plate (could include additional cross member supports)
- Longer Sizes
- Stationary Deck with Tilt

MODEL	DESCRIPTION	GVWR#	CURB WEIGHT#
ETB716TA3	7'x16' Tandem Axle Eagle Tilt bed w/ Brakes Both	10,000	2,190
ETB718TA3	7'x18' Tandem Axle Eagle Tilt bed w/ Brakes Both	10,000	2,275
ETB720TA3	7'x20' Tandem Axle Eagle Tilt bed w/ Brakes Both	10,000	2,380

EAGLE TILT BED 10K

STANDARD SPECIFICATIONS

GVWR	10,000#	Fenders	10" x 72" H.D. Diamond Plate Fenders
GAWR	10,400#	Frame	5" Channel
Axle	(2) 5,200# Posi- Lube Axle w/ Brakes Both Axles (4" Drop)	Cross Members	3" Channel
Coupler	Adjustable 2 5/16"	Ramps	Rear Approach Plates 14"
Suspension	Multi-Leaf Spring	Uprights	N/A
Coupler Height	Adjustable	Bump Rail	3" x 2" Tube
Deck Height	20"	Lights	Sealed Beam LED D.O.T
Tongue	2"x5" Rectangle Tube (.188 Thick Wall)	Decking	2x6 #2 or better Fir Decking
Jack	7K Drop Leg Tongue Jack	Electric Plug	7-Way RV
Safety Chain	.3125" x 35" 11.7 K Capacity	Paint	PPG Primer and Paint
Tires	ST 225/75 R15 Load Range D	Finish	Steel is cleaned (wiped down) to ensure quality protective finish
Wheels	15x5 6-5.5 Mod (Silver)		

STANDARD COLOR




Black ALK-FP901



Eagle Majestic Grey

OPTIONAL COLORS (additional charge)



White ALK-FP951



Bright Yellow ALK-FP801



Cat Yellow ALK-FP827



Ford Blue ALK-FP101



Ice Gray ALK-FP301



John Deer Green ALK-FP401



Kubota Orange ALK-FP601



Case IH Red ALK-FP701